

EVO frame series

Datasheet



FRAME-EVO-P20

EVO frame series

for Panasonic, Epson, Barco & Christie projectors

- ▶ new easily convertible design
- ▶ improved adjustments
- ▶ full stacking compatibility with earlier frame models
- ▶ built-in galvanic insulation
- ▶ DGUV V17 verified



FRAME-EVO-E10



FRAME-EVO-E10



FRAME-EVO-P20



FRAME-EVO-P20

The newest frame generation is the EVOLution of the very-well known earlier frame series. The system has been redesigned from scratch. The result is a very similar look with some major advantages. It is fully backwards-compatible for stacking and has nearly the same outer dimensions. The convertible design makes it simple to remove the upper ring for the use with ultra short throw lenses. For this process, there are no additional tools necessary and there are no parts to lose. Galvanic insulation from the projector housing to the trussing is built-in, so there is no need for plastic washers to avoid electrical ground loop problems. This simplifies the mounting of the projector into the frame. Furthermore, adjusting the projector in the frame is more precise with less unwanted play. Of course the EVO frame series is DGUV V17/V18 verified and has been subjected to a complete static analyses.

EVO frame series

Datasheet

Panasonic

EU market	FRAME-EVO-P10	FRAME-EVO-P11	FRAME-EVO-P14	FRAME-EVO-P17	FRAME-EVO-P20	FRAME-EVO-P30	FRAME-EVO-P32H
US market	FRAME-EVO-P10-US	FRAME-EVO-P11-US	FRAME-EVO-P14-US	FRAME-EVO-P17-US	FRAME-EVO-P20-US	FRAME-EVO-P30-US	FRAME-EVO-P32H-US
Dimensions [W x H x D] [mm]	652 x 353.5 x 683	652 x 393.5 x 683	783 x 373 x 678	778 x 398 x 725.5	750 x 435 x 883	757.1 x 540 x 883	757.1 x 540 x 893.5
Weight [kg] (frame only)	13.5	13.5	15.2	15.5	16	21	21.5
Maximum projector weight [kg] incl. lens	35	35	35	50	70	78	79
Possible orientation*1	Landscape, Portrait, Vertical down	Landscape, Portrait, Vertical down	Landscape, Portrait, Vertical down	Landscape, Portrait, Vertical down	Landscape, Portrait, Vertical down	Landscape, Portrait, Vertical down	Landscape, Portrait, Vertical down
Maximum stacking (see manual for more information)	Ceiling mount: max. 3 (only with EVO-LINK-200/201, EVO-LINK-210/211) Floor: max. 3	Ceiling mount: max. 3 (only with EVO-LINK-200/201, EVO-LINK-210/211) Floor: max. 3	Ceiling mount: max. 3 (only with EVO-LINK-200/201, EVO-LINK-210/211) Floor: max. 3	Ceiling mount: max. 3 (only with EVO-LINK-200/201, EVO-LINK-210/211) Floor: max. 3	Ceiling mount: max. 2 (only with EVO-LINK-200/201, EVO-LINK-210/211) Floor: max. 3	Ceiling mount: max. 2 (only with EVO-LINK-200/201, EVO-LINK-210/211, EVO-LINK-350) Floor: max. 2	Ceiling mount: max. 2 (only with EVO-LINK-350) Floor: max. 3
EXACT solutions accessories	EVO-LINK-200/201 EVO-LINK-210/211 PF-UNI-PORAD*2 PF-UNI-CLP5030 PF-UNI-CLP30PT	EVO-LINK-200/201 EVO-LINK-210/211 PF-UNI-PORAD*2 PF-UNI-CLP5030 PF-UNI-CLP30PT	EVO-LINK-200/201 EVO-LINK-210/211 PF-UNI-PORAD*2 PF-UNI-CLP5030 PF-UNI-CLP30PT	EVO-LINK-200/201 EVO-LINK-210/211 PF-UNI-PORAD*2 PF-UNI-CLP5030 PF-UNI-CLP30PT	EVO-LINK-200/201 EVO-LINK-210/211 PF-UNI-PORAD*2 PF-UNI-CLP5030 PF-UNI-CLP30PT	EVO-LINK-200/201 EVO-LINK-210/211 EVO-LINK-350 PF-UNI-PORAD-XL40 PF-UNI-CLP5040 PF-UNI-CLP40PT	EVO-LINK-350 PF-UNI-PORAD-XL40 PF-UNI-CLP5040 PF-UNI-CLP40PT
Compatibility selection, more on request	Panasonic PT-RZ660/PT-RZ770/ PT-RZ870/PT-RZ970/ PT-RZ120/ PT-RDQ10/PT-RDQ80/ PT-RDQ90	Panasonic (optimised for REQ12 series and REQ10 series) PT-REQ80/ PT-REQ10/ PT-REQ12/ PT-REQ12/ PT-REZ-10/ PT-REZ80/ PT-RZ990/ PT-RZ890/ PT-RZ790/ PT-RZ690/ PT-DZ13/PT-RZ660/ PT-RZ770/PT-RZ870/PT-RZ970/PT-RZ120	Panasonic PT-MZ20K/PT-MZ16/ PT-MZ13/PT-MZ10	Panasonic PT-RQ25K/PT-RQ18K/ PT-RZ24K/PT-RZ17K	Panasonic PT-RZ12/PT-RZ21/ PT-RS20/PT-RQ22/ PT-RQ13	Panasonic PT-RQ35K/PT-RQ45K/ PT-RZ34K	Panasonic PT-RQ35K/PT-RQ45K/ PT-RZ34K

*1 depending on the installation there might be additional accessories necessary

*2 depending on installed lens

EVO frame series

Datasheet

Epson, Barco & Christie

EU market	FRAME-EVO-E10	FRAME-EVO-E14	FRAME-EVO-P11BE	FRAME-EVO-B20	FRAME-EVO-C20	FRAME-EVO-C40H
US market	FRAME-EVO-E10-US	FRAME-EVO-E14-US	FRAME-EVO-P11BE-US	FRAME-EVO-B20-US	FRAME-EVO-C20-US	FRAME-EVO-C40H-US
Dimensions [W x H x D] [mm]	729 x 353.5 x 642	783 x 398 x 678	651 x 388.5 x 683	883 x 435 x 782.9	751 x 435 x 883	860 x 590 x 1063.5
Weight [kg] (frame only)	13.8	15.5	13.5	17	18	35
Maximum projector weight [kg] incl. lens	35	50	35	65	60	110
Possible orientation*1	Landscape, Portrait, Vertical down	Landscape, Portrait, Vertical down	Landscape, Portrait, Vertical down	Landscape, Portrait, Vertical down	Landscape, Portrait, Vertical down	Landscape, Portrait, Vertical down
Maximum stacking (see manual for more information)	Ceiling mount: max. 3 (only with EVO-LINK-200/201, EVO-LINK-210/211) Floor: max. 3	Ceiling mount: max. 3 (only with EVO-LINK-200/201, EVO-LINK-210/211) Floor: max. 3	Ceiling mount: max. 3 (only with EVO-LINK-200/201, EVO-LINK-210/211) Floor: max. 3	Ceiling mount: max. 2 (only with EVO-LINK-200/201, EVO-LINK-210/211) Floor: max. 3	Ceiling mount: max. 2 (only with EVO-LINK-200/201, EVO-LINK-210/211) Floor: max. 3	Ceiling mount: max. 2 (only with EVO-LINK-350) Floor: max. 3
EXACT solutions accessories	EVO-LINK-200/201 EVO-LINK-210/211 PF-UNI-PORAD*2 PF-UNI-CLP5030 PF-UNI-CLP30PT	EVO-LINK-200/201 EVO-LINK-210/211 PF-UNI-PORAD*2 PF-UNI-CLP5030 PF-UNI-CLP30PT	EVO-LINK-200/201 EVO-LINK-210/211 PF-UNI-PORAD*2 PF-UNI-CLP5030 PF-UNI-CLP30PT	EVO-LINK-200/201 EVO-LINK-210/211 PF-UNI-PORAD*2 PF-UNI-CLP5030 PF-UNI-CLP30PT	EVO-LINK-200/201 EVO-LINK-210/211 PF-UNI-PORAD*2 PF-UNI-CLP5030 PF-UNI-CLP30PT	EVO-LINK-350 PF-UNI-PORAD-XL40 PF-UNI-CLP5040 PF-UNI-CLP5040PT
Compatibility selection, more on request	Epson EB-L1000 series EB-PU2220 EB-PU2216 EB-PU2213	Epson EB-XQ2030	Barco I600 series	Barco G100 series	Christie M 4K25 RGB M 4K15 RGB	Christie Griffyn 4K35-RGB Griffyn 4K50-RGB

*1 depending on the installation there might be additional accessories necessary

*2 depending on installed lens